

	<p>YHT-N013-4 YHT-N023-4</p> <p>Current(A): 16A,32A Voltage(V): 110-130V~ 2P+E Protection degree: IP44</p>		<table border="1"> <tr> <td>Earth contact position</td> <td colspan="2">4h</td> </tr> <tr> <td>Rated current(A)</td> <td>16</td> <td>32</td> </tr> <tr> <td></td> <td colspan="2">Pole 3</td> </tr> <tr> <td rowspan="5">Dimension(mm)</td> <td>a</td> <td>118</td> <td>146</td> </tr> <tr> <td>b</td> <td>82</td> <td>100</td> </tr> <tr> <td>c</td> <td>47</td> <td>63</td> </tr> <tr> <td>d</td> <td>6-15</td> <td>10-20</td> </tr> <tr> <td>sw</td> <td>38</td> <td>50</td> </tr> <tr> <td>Cable nominal cross-section area(mm²)</td> <td>1-2.5</td> <td>2.5-6</td> </tr> </table>	Earth contact position	4h		Rated current(A)	16	32		Pole 3		Dimension(mm)	a	118	146	b	82	100	c	47	63	d	6-15	10-20	sw	38	50	Cable nominal cross-section area(mm ²)	1-2.5	2.5-6
Earth contact position	4h																														
Rated current(A)	16	32																													
	Pole 3																														
Dimension(mm)	a	118	146																												
	b	82	100																												
	c	47	63																												
	d	6-15	10-20																												
	sw	38	50																												
Cable nominal cross-section area(mm ²)	1-2.5	2.5-6																													
	<p>YHT-N013 YHT-N023</p> <p>Current(A): 16A,32A Voltage(V): 220-240V~ 2P+E Protection degree: IP44</p>		<table border="1"> <tr> <td>Earth contact position</td> <td colspan="2">6h</td> </tr> <tr> <td>Rated current(A)</td> <td>16</td> <td>32</td> </tr> <tr> <td></td> <td colspan="2">Pole 3</td> </tr> <tr> <td rowspan="5">Dimension(mm)</td> <td>a</td> <td>118</td> <td>146</td> </tr> <tr> <td>b</td> <td>82</td> <td>100</td> </tr> <tr> <td>c</td> <td>47</td> <td>63</td> </tr> <tr> <td>d</td> <td>6-15</td> <td>10-20</td> </tr> <tr> <td>sw</td> <td>38</td> <td>50</td> </tr> <tr> <td>Cable nominal cross-section area(mm²)</td> <td>1-2.5</td> <td>2.5-6</td> </tr> </table>	Earth contact position	6h		Rated current(A)	16	32		Pole 3		Dimension(mm)	a	118	146	b	82	100	c	47	63	d	6-15	10-20	sw	38	50	Cable nominal cross-section area(mm ²)	1-2.5	2.5-6
Earth contact position	6h																														
Rated current(A)	16	32																													
	Pole 3																														
Dimension(mm)	a	118	146																												
	b	82	100																												
	c	47	63																												
	d	6-15	10-20																												
	sw	38	50																												
Cable nominal cross-section area(mm ²)	1-2.5	2.5-6																													
	<p>YHT-N014 YHT-N024</p> <p>Current(A): 16A,32A Voltage(V): 380-415V~ 3P+E Protection degree: IP44</p>		<table border="1"> <tr> <td>Earth contact position</td> <td colspan="2">6h</td> </tr> <tr> <td>Rated current(A)</td> <td>16</td> <td>32</td> </tr> <tr> <td></td> <td colspan="2">Pole 4</td> </tr> <tr> <td rowspan="5">Dimension(mm)</td> <td>a</td> <td>124</td> <td>146</td> </tr> <tr> <td>b</td> <td>88</td> <td>100</td> </tr> <tr> <td>c</td> <td>53</td> <td>63</td> </tr> <tr> <td>d</td> <td>6-15</td> <td>10-20</td> </tr> <tr> <td>sw</td> <td>38</td> <td>50</td> </tr> <tr> <td>Cable nominal cross-section area(mm²)</td> <td>1-2.5</td> <td>2.5-6</td> </tr> </table>	Earth contact position	6h		Rated current(A)	16	32		Pole 4		Dimension(mm)	a	124	146	b	88	100	c	53	63	d	6-15	10-20	sw	38	50	Cable nominal cross-section area(mm ²)	1-2.5	2.5-6
Earth contact position	6h																														
Rated current(A)	16	32																													
	Pole 4																														
Dimension(mm)	a	124	146																												
	b	88	100																												
	c	53	63																												
	d	6-15	10-20																												
	sw	38	50																												
Cable nominal cross-section area(mm ²)	1-2.5	2.5-6																													
	<p>YHT-N015 YHT-N025</p> <p>Current(A): 16A,32A Voltage(V): 220-380V~ 240-415V~ 3P+N+E Protection degree: IP44</p>		<table border="1"> <tr> <td>Earth contact position</td> <td colspan="2">6h</td> </tr> <tr> <td>Rated current(A)</td> <td>16</td> <td>32</td> </tr> <tr> <td></td> <td colspan="2">Pole 5</td> </tr> <tr> <td rowspan="5">Dimension(mm)</td> <td>a</td> <td>131</td> <td>152</td> </tr> <tr> <td>b</td> <td>95</td> <td>106</td> </tr> <tr> <td>c</td> <td>61</td> <td>70</td> </tr> <tr> <td>d</td> <td>8-16</td> <td>10-20</td> </tr> <tr> <td>sw</td> <td>42</td> <td>50</td> </tr> <tr> <td>Cable nominal cross-section area(mm²)</td> <td>1-2.5</td> <td>2.5-6</td> </tr> </table>	Earth contact position	6h		Rated current(A)	16	32		Pole 5		Dimension(mm)	a	131	152	b	95	106	c	61	70	d	8-16	10-20	sw	42	50	Cable nominal cross-section area(mm ²)	1-2.5	2.5-6
Earth contact position	6h																														
Rated current(A)	16	32																													
	Pole 5																														
Dimension(mm)	a	131	152																												
	b	95	106																												
	c	61	70																												
	d	8-16	10-20																												
	sw	42	50																												
Cable nominal cross-section area(mm ²)	1-2.5	2.5-6																													
	<p>YHT-N0132-4 YHT-N0232-4</p> <p>Current(A): 16A,32A Voltage(V): 110-130V~ 2P+E Protection degree: IP67</p>		<table border="1"> <tr> <td>Earth contact position</td> <td colspan="2">4h</td> </tr> <tr> <td>Rated current(A)</td> <td>16</td> <td>32</td> </tr> <tr> <td></td> <td colspan="2">Pole 3</td> </tr> <tr> <td rowspan="5">Dimension(mm)</td> <td>a</td> <td>118</td> <td>146</td> </tr> <tr> <td>b</td> <td>82</td> <td>100</td> </tr> <tr> <td>c</td> <td>47</td> <td>63</td> </tr> <tr> <td>d</td> <td>6-15</td> <td>10-20</td> </tr> <tr> <td>sw</td> <td>38</td> <td>50</td> </tr> <tr> <td>Cable nominal cross-section area(mm²)</td> <td>1-2.5</td> <td>2.5-6</td> </tr> </table>	Earth contact position	4h		Rated current(A)	16	32		Pole 3		Dimension(mm)	a	118	146	b	82	100	c	47	63	d	6-15	10-20	sw	38	50	Cable nominal cross-section area(mm ²)	1-2.5	2.5-6
Earth contact position	4h																														
Rated current(A)	16	32																													
	Pole 3																														
Dimension(mm)	a	118	146																												
	b	82	100																												
	c	47	63																												
	d	6-15	10-20																												
	sw	38	50																												
Cable nominal cross-section area(mm ²)	1-2.5	2.5-6																													
	<p>YHT-N0132 YHT-N0232</p> <p>Current(A): 16A,32A Voltage(V): 220-240V~ 3P+E Protection degree: IP67</p>		<table border="1"> <tr> <td>Earth contact position</td> <td colspan="2">6h</td> </tr> <tr> <td>Rated current(A)</td> <td>16</td> <td>32</td> </tr> <tr> <td></td> <td colspan="2">Pole 3</td> </tr> <tr> <td rowspan="5">Dimension(mm)</td> <td>a</td> <td>118</td> <td>146</td> </tr> <tr> <td>b</td> <td>82</td> <td>100</td> </tr> <tr> <td>c</td> <td>6-15</td> <td>10-20</td> </tr> <tr> <td>d</td> <td>38</td> <td>50</td> </tr> <tr> <td>sw</td> <td>38</td> <td>50</td> </tr> <tr> <td>Cable nominal cross-section area(mm²)</td> <td>1-2.5</td> <td>2.5-6</td> </tr> </table>	Earth contact position	6h		Rated current(A)	16	32		Pole 3		Dimension(mm)	a	118	146	b	82	100	c	6-15	10-20	d	38	50	sw	38	50	Cable nominal cross-section area(mm ²)	1-2.5	2.5-6
Earth contact position	6h																														
Rated current(A)	16	32																													
	Pole 3																														
Dimension(mm)	a	118	146																												
	b	82	100																												
	c	6-15	10-20																												
	d	38	50																												
	sw	38	50																												
Cable nominal cross-section area(mm ²)	1-2.5	2.5-6																													