

## Relay

# 55.32,55.34 General-purpose Relay

### Features

- Various relays, including LED, test button
- With 2Z, 4Z contact forms
- With various terminal types
- Gilt contact types
- Transparent dust-proof cover,
- Various mounting types
- Various sockets available




55.32



55.34

### Model Meaning



### Contact Rating

Contact Rating	2Z	4Z
Contact Resistance	50mΩ(1A 6VDC)	50mΩ(1A 6VDC)
Contact capacity	10A/220VAC	5A/220VAC
	30VDC	30VDC 125VAC

### Specification

Insulation Resistance	500MΩ, 500VDC
Dielectric Strength	BCC 1000VAC 1min
	BOC 1500VAC 1min
	CCC 1500VAC 1min
Operate Time	25ms/25ms
Terminal Type	PCB and Socket


### Coil Rating

Nominal Coil Power: 0.9W/1.2VA

### Coil Version

Nominal Voltage VDC	Pull-in Voltage VDC	Release Voltage VDC	Coil Resistance Ω:±10%	Nominal Voltage VDC	Pull-in Voltage VDC	Release Voltage VDC	Coil Resistance Ω:±10%
5	4.0	0.50	30	6	4.80	1.80	12
6	4.8	0.60	40	12	9.60	3.60	42
12	9.6	1.20	160	24	19.2	7.20	168
24	19.2	2.40	640	48	38.4	14.4	675
48	38.4	4.80	2560	120	96.0	36.0	3500
110	88.0	11	12100	220/240	176.0	66.0	14000/16500

### Dimension



### Reference Data

