

## DTS726-LCD Electronic Three-phase Meter



### DTS726 Three-phase Electronic Energy Meter

#### General

The meter is used in three phase four wire power grid. The meter is designed to measure AC active energy. All of its functions comply with the relative technical requirement for class 1 three phase watt hour meter in IEC62053-21. It is a long life meter with the advantage of high stability, high over load capability, low power loss.

#### Basic Function

1. Mechanical step register 5+1(default) , 6 digit no decimal OR LCD display 6+1, 5+2;
2. Bi-directional total active energy measurement ,reverse active energy measure in the total active energy;
3. Three phase power supply , the meter also measure when loss one phase (any one wire in three phase three wire ) or when loss two phase (any two in three phase four wire);
4. Loss phase LED indicates working of phase;
5. Pulse LED indicates working of meter, Pulse output with optical coupling isolation;
6. Two type of cases (protective-class I and II) are available.

#### Optional Function

1. Internal connection between the voltage circuit hook and current circuit hook in order to anti-tamer.

#### Specifications

Technical Index	Specification
Rate voltage	DTS726 three phase four wire 3×57.7/100V, 3×127/220V, 3×120/208V, 3×220/380V, 3×230/400V, 3×240/415V
Working voltage range	0.8~1.2Un
Rate Current	5A/CT,1.5(6)A,5(30)A,10(40)A,5(60)A,20(80)A,10(100)A, or other as required
Frequency	50Hz or 60Hz
Connection mode	CT type or Direct type
Display	mechanical step register or LCD
Accuracy class	Active class 1.0
Power consumption	0.5W/8VA each phase
Start current	0.004Ib
AC voltage withstand	4000V/25mA for 60 sec
Impulse Voltage	6kV 1.2μs waveform
IP grade	IP51 or IP54
Constant	400~6400 imp/kWh
Pulse output	Passive pulse, pulse width is 80+5 ms
Executive standard	IEC62053-21, IEC62052-11
Work temperature	-30°C~70°C
Outline dimension L×M×H	215×145×69mm (short terminal cover L1) 260×145×69mm (long terminal cover L2)
Weight	Approx 1.2kg

