

# JQX-62F Power Relay

JQX-62F 1Z DC12V

Coil Voltage 5,6,9,12,24,48,60VDC  
12V,24V,110V,220VAC  
Contact 1Z,1H,1D 2Z,2H,2D  
Relay type

## Contact Ratings

Contact Ratings	1Z,1H,1D 2Z,2H,2D
Contact Resistance	30mΩ (1A 6VDC)
Contact capacity	80A 120A 250VAC 2HP 250VAC

## Specification

Insulation Resistance	1000MΩ, 500VDC
Dielectric Strength	BCC 2500VAC 1minute
	BOC 1200VAC 1minute
Operate Time	25ms /25ms
Terminal Type	Quick connection type outlet

## Coil Ratings

Nominal Coil Power	DC2.0W AC2.5VA
--------------------	----------------

## Coil Versions

Nominal Voltage VDC	Pull-in Voltage VDC	Release Voltage VDC	Coil Resistance Ω:±10%	Nominal Voltage VAC	Pull-in Voltage VAC	Release Voltage VAC	Coil Resistance Ω:±10%
6	4.20	0.60	18	6	4.80	1.80	9
12	8.40	1.20	70	12	9.60	3.60	36
24	16.8	2.40	290	24	19.20	7.20	144
48	33.6	4.80	1152	48	38.40	14.40	576
60	42.0	6.00	2800	110	88.00	36.00	3500
110	88.0	11.0	9650	220/240	176.00	72.00	12000/14400

## Dimension.Bottom View



## Reference Data

