



Application

These products are suitable for the connection of copper conductors (section area 1.5mm²-1000mm²) in power cable with electronic equipment and they are made of copper tube T2 and coated with tin. Their working temperature -55°C-150°C.

SC(JGK) Imported Copper Terminals

Model & Spec.	Dimension(mm)					
	Φ	D	d	L	(W)	S
SC(JGK)-1.5	4.2, 5.2	3.5	2.5	18	7	1
SC(JGK)-2.5	4.2, 5.2	4	3	19	8	1
SC(JGK)-4	5.2, 6.4	4.8	3.5	20	8	1.2
SC(JGK)-6	5.2, 6.4	5.5	4.1	23	9	1.4
SC(JGK)-10	6.4, 8.4	6.7	5	25.5	11	1.6
SC(JGK)-16	6.4, 8.4	7.5	5.8	30	12	1.8
SC(JGK)-25	6.4, 8.4, 10.5	9	7.2	32.5	13	1.8
SC(JGK)-35	6.4, 8.4, 10.5	10.5	8.5	37	15	2
SC(JGK)-50	8.4, 10.5	12.5	10.1	45	18	2.4
SC(JGK)-70	10.5, 12.5	14.5	11.7	49	21	2.8
SC(JGK)-95	10.5, 12.5	17	13.8	54	25	3.2
SC(JGK)-120	12.5, 16.5	19.5	15.9	62	28	3.6
SC(JGK)-150	12.5, 16.5	20.5	16.7	68	30	3.8
SC(JGK)-185	16.5	23.5	19.1	76	34	4.4
SC(JGK)-240	16.5	26	21.4	90	38	4.6
SC(JGK)-300	16.5, 20.5	30	24.6	100	44	5.4
SC(JGK)-400	16.5, 20.5	34	27.4	110	50	6.6
SC(JGK)-500	16.5, 20.5	38	30.8	120	55	7.2
SC(JGK)-630	20.5	45	35.6	135	65	9.2
SC(JGK)-800	22.5	50	40.4	170	72	9.6
SC(JGK)-1000	22.5	55	45	200	80	10