


Relay

SUL180a,SUL160a,YCST8,YCC18 Timers

Classification		Timer			
Model		SUL180a	SUL160a	YCST8	YCC18
Appearance					
Contact capacity		AC230 16(4)A	AC220 16(4)A	AC220 16A	AC220 16A
Full timing range		24h	24h	7min	20min
Contact resistance		≤50mΩ	≤50mΩ	≤50mΩ	≤50mΩ
Insulation resistance		≥100MΩ	≥100MΩ	≥100MΩ	≥100MΩ
Coil voltage		110, 230V AC	110, 230V AC	110, 230V AC	110, 230V AC
Life	Electrical	10 ⁵ times	10 ⁵ times	10 ⁵ times	10 ⁵ times
	Mechanical	10 ⁷ times	10 ⁷ times	10 ⁷ times	10 ⁷ times
Operating temperature		-10°C~+50°C	-10°C~+55°C	-20°C~+55°C	-20°C~+55°C
Dimensions(mm)					
Storage battery (working reserve)		time 70h	without battery		
Minimum setting unit		15Minutes	15Minutes	0.5Minutes	0.5Minutes
Set up times		15m/per time 96 times	15m/per time 96 times	1M,1.5M,2M,2.5M 3M,3.5M,4M,4.5M,5M 5.5M,6M,6.5M,7M	0.5M,5M,10M 15M,20M
Consumed power max		1VA	1VA	1VA	5VA stand by mode 1VA

