

YCX6 Lighting Distribution Box

A



General

YCX6 is applicable to residential buildings or places for non-professional people to enter, it includes control equipment and signal equipment. It is applicable to the circuit with an alternating current, the nominal voltage to earth does not exceed 380V, the output circuit is with short circuit protection function. When the total input load current does not exceed 125A, the rated current of each short circuit protection device shall not exceed 63A. This product is with plastic cover and metal box, mainly used to following conditions:

- power distribution system

Building electrical distribution system, house renovation and decoration.

- installation mode

The metal box matched with the plastic cover, it is especially suitable for flush mounting of distribution box in construction and decoration projects.

- appearance design

The stylish appearance design is suitable for high-end residences, hotels and office buildings, etc., which show the taste of modern life.

Specification

Product mode	Rows	No. of units	Surface mounting dimension	Flush mounting dimension(hole size)
YCX6-9	1	9	240×200×75	217×180×75
YCX6-12	1	12	295×230×75	270×210×75
YCX6-16	1	16	360×230×75	340×210×75
YCX6-20	1	20	438×230×75	413×210×75
YCX6-24	2	24	295×460×75	270×440×75
YCX6-32	2	32	366×460×75	340×440×75
YCX6-36	3	36	295×690×75	270×670×75
YCX6-40	2	40	438×460×75	413×440×75
YCX6-48	3	48	366×690×75	340×670×75
YCX6-60	3	60	438×690×75	438×670×75

A